

22KW DOUBLE-OUTPUT EV CHARGER

The AC EV charger is a new product launched by Fox ESS. Its appearance of this product adopts a streamlined and simple design, which is more refined and glitzy. Through the App, car owners can choose the Bluetooth smart lock, timing charging function, or change it to plug and play mode. At the same time, it can monitor charging information, set EV charger parameters, bind equipment and authorization, and upgrade remote software.

Dual output design
Space saving, dual charging



Innovativeness Design

Streamline design



Intelligent Control

Wireless communication (WiFi/Bluetooth)
OCPP communication protocol with the backend
Smart charge or scheduled charge by App



Energy Saving

Standby power consumption is less than 2W, excellent energy-saving efficiency



Flexible Option

Type 1 or Type 2 charging cable
App operation or plug and play
Wall-mounted or floor-stand installation



Secure and Safe

6mA DC residual current protection
Anti-welding protection
IP65 rated

- Power: 22kW or 11kW*2
- Output Current: Max.32A or 16A*2
- Output Voltage: 400V AC
- Type 2 cable charging connector
- Compliant with OCPP 1.6 (JSON)/2.0
- App operation or RFID authentication or plug, play & 4G
- Protection Grade: IP65
- -25 ~ 50°C wide Operating Temperature



For more about the Fox ESS EV charger
Please visit:

WWW.FOX-ESS.COM



22KW DOUBLE-OUTPUT EV CHARGER

TECHNICAL SPECIFICATIONS



MODEL	A022KP2-E	A022KS2-E
TYPE	CHARGING PLUG	CHARGING SOCKET
INPUT		
Wiring Scheme	3P+N+PE	
Voltage	400Vac, ±20%	
Maximum Current	32A	
Frequency	50/60Hz	
OUTPUT		
Voltage	400Vac, ±20%	
Maximum Current	32A or 16A	
Rated Power	22kW or 11kW*2	
USER INTERFACE & CONTROL		
Connector Type	Type 2 cable	Type 2 socket
RFID Reader	Mifare ISO/IEC 14443 A	
Start Mode	Plug&Play/RFID card/App	
Emergency Stop	Yes	
COMMUNICATION		
WiFi, Bluetooth	Yes	
4G, Ethernet	Optional	
OCPP	OCPP 1.6 JSON, OCPP 2.0 optional	
ENVIRONMENT		
Installation	Wall-mount / Post-mount	
Operating Temperature	-25°C ~ 50°C	
Operating Humidity	5% ~ 95% No condensation	
Operating Altitude	≤2000m	
DIMENSION AND WEIGHT		
Product Dimension	480*275*180 mm	
Product Weight	11.6kg	7kg
SAFETY		
IP protection rating	IP65	
IK protection rating	IK08	
Residual Current Detection	AC 30mA/DC 6mA	
Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
EMC	Class B	
Certification	CE	
Certification Standard	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021	