

SECOND GENERATION EV CHARGER

The AC EV charger is a new product launched by Fox ESS . Its appearance of this product adopts a streamlined and simple design, which is more refined and glitzy. Through the App, car owners can choose the Bluetooth smart lock, timing charging function, or change it to plug and play mode. At the same time, it can monitor charging information, set EV charger parameters, bind equipment and authorization, and upgrade remote software.



Innovativeness Design

Streamline design



Intelligent Control

Wireless communication (WiFi/Bluetooth)
 OCPP communication protocol with the backend
 Smart charge or scheduled charge by App



Energy Saving

Standby power consumption is less than 2W, excellent energy-saving efficiency



Flexible Option

Type 1 or Type 2 charging cable
 App operation or plug and play
 Wall-mounted or floor-stand installation



Secure and Safe

6mA DC residual current protection
 Anti-welding protection
 IP65 rated

- Power: 11kW
- Output Current: Max.16A
- Output Voltage: 400V AC
- Type 2 cable charging connector
- Compliant with OCPP 1.6 (JSON)/2.0
- App operation or RFID authentication or plug, play & 4G
- Protection Grade: IP65
- -25 ~ 50°C wide Operating Temperature



For more about the Fox ESS EV charger
 Please visit:

WWW.FOX-ESS.COM



SECOND GENERATION 11KW EV CHARGER

TECHNICAL SPECIFICATIONS



MODEL	A011KP1-E-2	A011KS1-E-2
TYPE	CHARGING PLUG	CHARGING SOCKET
INPUT		
Wiring Scheme	3P+N+PE	
Voltage	400Vac, ±20%	
Maximum Current	16A	
Frequency	50/60Hz	
OUTPUT		
Voltage	400Vac, ±20%	
Maximum Current	16A	
Rated Power	11kW	
USER INTERFACE & CONTROL		
Connector Type	Type 2 cable	Type 2 socket
RFID Reader	Mifare ISO/IEC 14443 A	
Start Mode	Plug&Play/RFID card/App	
Emergency Stop	Yes	
COMMUNICATION		
WiFi, Bluetooth	Yes	
4G, Ethernet	Optional	
OCPP	OCPP 1.6 JSON, OCPP 2.0 optional	
ENVIRONMENT		
Installation	Wall-mount / Post-mount	
Operating Temperature	-25°C ~ 50°C	
Operating Humidity	5% ~ 95% No condensation	
Operating Altitude	≤2000m	
DIMENSION AND WEIGHT		
Product Dimension	320*190*130 mm	320*190*144.5 mm
Product Weight	3.55kg	2.0kg
SAFETY		
IP protection rating	IP65	
IK protection rating	IK08	
Residual Current Detection	AC 30mA/DC 6mA	
Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
EMC	Class B	
Certification	CE	
Certification Standard	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021	